

DATE: 8/20/2024

INVITATION TO BID
THIS IS NOT AN ORDER

Page: 5

BID NO.: 50-00145984

JEFFERSON PARISH

PURCHASING DEPARTMENT
P.O. BOX 9
GRETNA, LA. 70054-0009
504-364-2678

VENDOR: 27118 BLANK BID COPY VENDOR

PURCHASING SPECIALIST:
KLEE

As per LSA-RS 47:301 et seq., all governmental bodies are excluded from payment of sales taxes to any Louisiana taxing body. Quotations shall be based on F.O.B. Agency warehouse or jobsite, anywhere within the Parish as designated by the Purchasing Department.

JEFFERSON PARISH reserves the right to cancel all or any part of an order if not shipped promptly. No charges will be allowed for parking or cartage unless specified in quotation. The order must not be filled at a higher price than quoted. JEFFERSON PARISH reserves the right to cancel at any time and for any reason by issuing a THIRTY (30) day written notice to the contractor.

JEFFERSON PARISH is expecting all products to be new and all work to be done in workman-like manner, according to standard practices. Any deviations or alteration from the specifications must be indicated on the bid form for each item and upon request, product data for same must be submitted by the time specified by the Purchasing Department.

DELIVERY: FOB JEFFERSON PARISH	
INDICATE DELIVERY DATE ON EQUIPMENT AND SUPPLIES	<u>Approx 3 Weeks</u>
INDICATE STARTING TIME (IN DAYS) FOR CONSTRUCTION WORK	<u>N/A</u>
INDICATE COMPLETION TIME (IN DAYS) FOR CONSTRUCTION WORK	<u>N/A</u>

In the event that addenda are issued with this bid, bidders MUST acknowledge all addenda on the bid form. Bidder must acknowledge receipt of an addendum on the bid form by placing the addendum number as indicated. Failure to acknowledge any addendum on the bid form will result in bid rejection.


Acknowledge Receipt of Addenda: NUMBER: N/A

NUMBER: N/A

NUMBER: N/A

NUMBER: N/A

LOUISIANA CONTRACTOR'S LICENSE NO.: (if applicable) N/A

*** ALL BIDDERS MUST COMPLETE SECTION BELOW ***	
FIRM NAME: Rocky Mountain Recreation LLC	
SIGNATURE: (Must be signed here) 	TITLE: Controller
PRINT OR TYPE NAME: Janeil Norman	
ADDRESS: PO Box 68	
CITY, STATE: Albion ID	ZIP: 83311
TELEPHONE: (208) 670-5079	FAX: () N/A
EMAIL ADDRESS: rockymtnrecllc@gmail.com	

TOTAL PRICE OF ALL BID ITEMS: \$ 8,879.90

INVITATION TO BID FROM JEFFERSON PARISH - continued

BID NO.: 50-00145984

SEALED BID

ITEM NUMBER	QUANTITY	U/M	DESCRIPTION OF ARTICLES	UNIT PRICE QUOTED	TOTALS
1	2.00	EA	PURCHASE OF VOLLEYBALL FOR WESTBANK PARKS AND RECREATION 0001-POWER VOLLYBALL SYSTEMS W/POSTS, NETS, ANTENNAE AND BOUNDARY MARKERS DRAPER, INC. PVS-01 Bidding Alternate SNA Sports Group - See Attached Specs	\$ 3,899.95	\$ 7,799.90
2	4.00	EA	0002- DRAPER, INC UPRIGHT POST PADS Bidding Alternate SNA Sports Group - See Attached Specs	Included	Included
3	1.00	EA	0003 - Freight	\$ 1,080.00	\$ 1,080.00
PLEASE DELIVER: WB JPRD 7437 LAPALCO BLVD MARRERO, LA 70072					



(800)823-0182 / www.SNAsportsgroup.com

Specifications for Collegiate 4000

MODEL NO. SNAVB40C4

Removable type, in-floor sleeves. Uprights shall be one single piece each, 120" long and anodized 6061-T6 aluminum, 3-15/16" in diameter, weighing 22 and 28 lbs. Net shall attach at only two points on the sliding Winch Rail, which shall be mounted in profiled grooves running infinitely over the full range. Net tensioning device shall be mounted on the Winch Rail, and shall be a low profile, non-slip, threaded rod-type worm drive linear-actuator type utilizing conical toothed steel gears for safety and durability. The range of this gear mechanism shall be 17-1/2". Gear mechanism shall be completely encased in anodized aluminum. Net shall attach at only two points on the sliding End Rail, which shall be mounted in profiled grooves running infinitely over the full range. A two position (lock/off) lever lock shall be used to provide slip-free adjustment of the net height; screw-in adjustment knobs shall be deemed unacceptable. Uprights shall adjust to allow for Men, Women, and Juniors heights, as well as for badminton and tennis set ups. Uprights shall have floor-protective molded plastic caps. Hand cranks shall be permanently attached. Standards and winch shall carry no less than a limited lifetime warranty. Entire system shall meet or exceed all NCAA and NFHS requirements for competition.

COLLEGIATE 4000 CENTER UPRIGHT

MODEL NO. SNAVB45C4N

Removable type, in floor sleeves. Uprights shall be one single piece, 120" long and shall be anodized 6061-T6 aluminum, 3-15/16" in diameter, weighing 23 lbs. Shall have End Rail net attachments on two sides of this upright. Rails shall move independently of each other, allowing different net heights on each side of the uprights. Uprights shall adjust to allow for Men, Women, and Juniors heights, as well as for badminton and tennis set ups. Uprights shall have floor-protective molded plastic caps. All warranties from above shall apply.

COLLEGIATE 4000 CENTER UPRIGHT WITH WINCH

MODEL NO. SNAVB45C4W

Removable type, in floor sleeves. Uprights shall be one single piece, 120" long and shall be anodized 6061-T6 aluminum, 3-15/16" in diameter, weighing 29 lbs. Shall have Winch Rail net attachments on one side and End Rail net attachments on the other side of the upright. Rails shall move independently of each other, allowing different net heights on each side of the uprights. Upright shall have floor-protective molded plastic caps. Uprights shall adjust to allow for Men, Women, and Juniors heights, as well as for badminton and tennis set ups. Hand cranks shall be permanently attached. All warranties from above shall apply.

VOLLEYBALL FLOOR SLEEVE

MODEL NO. VB27FS

Aluminum sleeve shall be 13" long. Inside diameter of the sleeve shall be 4".

UNIVERSAL HINGED BRASS COVER PLATE

MODEL NO. VB23CV

Cover plate shall be brass alloy with attached, hinged cover. Four (4) holes in the ring (for screwing into the floor) shall be completely concealed under the cover when in the closed position. In a floating wood floor, the plate is connected to the floor only allowing it to move with the expansion and contraction of the floor. Plates shall be 8" in diameter. Overall thickness shall be 3/8". Hinged cover plate – not including the outer ring - shall be 6 31/32" in diameter. Diameter of clear opening shall be 6".

MODEL NO. VB27

This package shall include both the VB27FS floor sleeve and VB23CV cover plate listed above.

INTERNATIONAL NET WITH RATCHET TENSIONER

MODEL NO. SNAVB1298A

Net shall be 9.8 meters in length and 1-meter maximum width. Netting shall be 10 centimeter square mesh, black nylon, KNOTLESS. Wide side tapes with sewn-in wooden dowels for equal net tension. Top cable shall be 1/8" steel, specially sewn into 50-millimeter white nylon binding. Bottom tension rope shall be nylon, covered by 30-millimeter white nylon binding.



NET ANTENNAE WITH SIDELINE MARKERS

MODEL NO. SNAVB12

Net antennae shall be 3/8" in diameter fiberglass rods, 71" long, with alternating red and white bands. Sideline markers shall be white nylon reinforced vinyl 2 1/2" wide with full-length pocket to contain antennae. Attachment to the net shall be full-length Velcro closures.

CABLE COVERS

MODEL NO. VB35P

Cable covers shall be made of 1/2" thick polyurethane foam. Shall be covered in 14 oz. reinforced polyester laminated white vinyl.

UPRIGHT SAFETY PADS

MODEL NO. SNAVB51P

Each upright pad shall be a single piece, 72" in height and 26" in width. Padding shall be comprised of cross-linked polyethylene foam, 1.25" thick. Covering shall be nylon-reinforced vinyl. Attachments to uprights shall be affected by Velcro straps. 16 colors available: Scarlet, Cardinal, Maroon, Orange, Burnt Orange, Gold, Vegas Gold, Kelly Green, Forest Green, Columbia Blue, Royal Blue, Dark Royal, Navy Blue, Purple, Gray, Brown, Pink, and Black.

CENTER UPRIGHT SAFETY PADS

MODEL NO. VB510P

Same specifications exist as the model SNAVB51P upright pad. Exception: each center upright pad shall consist of two identical pieces, 72" in height and 10.5" in width. Attachment to the uprights shall be affected by Velcro straps that are attached on both pads. 18 colors available.

VB73A REFEREE STAND WITH PADS

MODEL NO. VB73A

Shall be of tubular steel construction with steel platform. Stand shall attach to the upright by means of a heavy-duty steel clamp with rubber pads to protect the upright. Clamp shall close by means of a threaded rod-driven mechanism, and shall fold away when not in use. Stand shall have wheels to allow for easy transport, and shall have non-slip rubber floor pads. Stand shall have adjustable legs allowing for platform adjustments from 47" to 53". **Available in Gray, Black, Scarlet, Maroon, Royal Blue, and Navy Blue padding.**

VB76 FREESTANDING FOLDING REFEREE STAND

MODEL NO. VB76

Shall be of tubular steel construction with steel platform. Shall be completely freestanding, with rear wheels for transport. Stand shall be able to fold together for ease of storage and transport. Dimensions shall be 47.5" L x 27.5" W x 88-3/4" in height. Padding for the legs and platform shall be of dense foam body covered with nylon-reinforced vinyl. **Available in Gray, Black, Scarlet, Maroon, Royal-Blue, and Navy-Blue padding.**

DELUXE 6-POST EQUIPMENT CART

MODEL NO. VB96

Shall be of tubular steel construction with two vinyl tarp storage areas for nets and antennas. Cart will accommodate 6 posts and have the capability to hold posts with pads on them. Top of cart shall accommodate storage of a referee stand with pads. Gross dimensions of cart shall be 46" high – 32 1/2" wide – 41 17-32" long.

4-POST EQUIPMENT CART

MODEL NO. VB94

Shall be of tubular steel construction with metal platform for accessories. Cart will accommodate 4 posts and have the capability to hold posts with pads on them. Gross dimensions of cart shall be 42" high x 32" wide x 46" long.



VOLLEYBALL T-BASE

MODEL NO. VBTBASE

Designed for use in facilities where the sub-floor structure is not adequate to accommodate the installation of a floor sleeve. T-Base shall be constructed of welded steel capable of accepting a 4" diameter volleyball post. The gross dimensions will be 12" H x 17 ¾" L x 18" W. The base is securely locked in place with a ½" turn bolt screwed into a ½" diameter, 13 thread-per-inch floor anchor.

T-BASE PADDING

MODEL NO. VBTBASEP

Each T-Base pad shall be two pieces – one wrap-around pad for T-Base sides, and one trapezoidal pad for T-Base top. Padding shall be comprised of cross-linked polyethylene foam, 1.25" thick. Covering shall be nylon-reinforced vinyl. Attachments to each other shall be affected by Velcro. 16 colors available: Scarlet, Cardinal, Maroon, Orange, Burnt Orange, Gold, Vegas Gold, Kelly Green, Forest Green, Columbia Blue, Royal Blue, Dark Royal, Navy Blue, Purple, Gray, Brown, Pink, and Black.



Specifications for Custom Base Adapters

CUSTOM BASE ADAPTER

MODEL NO. SNAVBADPTS

Aluminum Custom Base Adapter shall be 16.5 inches in total length. Top portion shall match inner contour of volleyball post for 6.5 inches. Bottom portion shall be thick-walled aluminum with a 3-inch outside diameter; protruding for 10 inches. A black plastic cap shall be attached at the bottom for floor protection. Adapter shall be inserted into the bottom of the Schelde aluminum volleyball post to allow for the 4-inch post to enter a 3-inch in-ground floor sleeve. Adapter shall be permanently attached to the volleyball post by means of epoxy and roll pins. Custom Base Adapter shall carry a limited lifetime warranty.

3" TO 3.5" CUSTOM BASE ADAPTER SLEEVE

MODEL NO. SNAVB335

Custom Base Adapter Sleeve shall be a cylindrical aluminum sleeve with a 3.5-inch outside diameter and a 3-inch inside diameter. Sleeve is designed to slide onto the Custom Base Adapter to alter the outside diameter of the protruding section from 3-inch to 3.5-inch. Adapter Sleeve can be permanently affixed to the Adapter by means of two (2) roll pins.