

ELECTRIC SERIES SCISSOR LIFTS

2132E / 2732E

Compliant with ANSI/CSA standards

PRODUCT HIGHLIGHTS

Efficient and Environmentally Friendly

- High work efficiency
- Environmental protections for zero emissions

Reduced Maintenance Costs

- The short design of the sliding rail makes debris easy to clean
- Rapid and convenient transportation with two-way forklift slot
- Lower cost of ownership with highly versatile parts and components

Reliable Performance

- New wide scissor design allows for a more stable at-height work experience
- Bumper rail and indented sliding rail designed for anti-scratch



Standard Features

Maintenance-free battery	Automatic braking system	Drive at full height
Proportional control	Emergency lowering system	Forklift pocket and lifting eyes
Bumper rail	Emergency stop at both platform and ground controls	Electrophoresic paint technology
2WD x 2WS	Fault diagnosis system	Foldable guardrail
Non-marking tires	Tilt protection	Overload sensing system
Integrated hand shield	Automatic pothole guard	

Optional Features

Overhead anti-collision device	Headlight	RCBO
AC cable to platform	Foot switch	

SINOBOOM™
NORTH AMERICA

PARTNERS IN ACCESS™

SINOBOOM.US | INFO@SINOBOOM.US
310 MASON CREEK DR, UNIT #100, KATY, TX 77450

ELECTRIC SERIES SCISSOR LIFTS

2132E/2732E

Compliant with ANSI/CSA standards

Model	2132E	2732E
Dimensions		
Max Working Height(Indoor/Outdoor)*	27' 3"(8.3m)	33' 2" / 26' 3"(10.1m / 8m)*
A-Max Platform Height(Indoor/Outdoor)*	20' 8"(6.3m)	26' 7" / 19' 8"(8.1m / 6m)*
B-Max Horizontal Extension	3'(0.9m)	3'(0.9m)
C-Length Stowed	8'(2.46m)	8'(2.46m)
D-Width Stowed	2' 9"(0.83m)	2' 9"(0.83m)
E-Height Stowed (Rail Folded)	6'(1.84m)	6' 5"(1.96m)
E-Height Stowed (Rail Unfolded)	7' 4"(2.24m)	7' 9"(2.36m)
F-Wheelbase	6' 2"(1.88m)	6' 2"(1.88m)
Ground Clearance(Pothole Guard Stowed)	4"(0.1m)	4"(0.1m)
Ground Clearance (Pothole Guard Deployed)	0.98"(25mm)	0.98"(25mm)
Platform Dimensions(LxWxH)	7' 7" x 2' 8" x 3' 7"(2.3mx0.8mx1.1m)	7' 7" x 2' 8" x 3' 7"(2.3mx0.8mx1.1m)
Performance		
Platform Allowable Occupancy	2 persons(Indoor) 1 persons (Outdoor)	2 persons(Indoor) 1 persons (Outdoor)
Platform Capacity	838lbs(380kg)	551lbs(250kg)
Extension Platform Capacity	265lbs(120kg)	265lbs(120kg)
Drive Speed - Stowed	2.5mph(4km/h)	2.5mph(4km/h)
Drive Speed - Raised	0.5mph(0.8km/h)	0.5mph(0.8km/h)
Lift Time (Unloaded)	25s~30s	30s~35s
Descent Time (Unloaded)	30s~35s	34s~39s
Gradeability	25%	25%
Turning Radius (Inside/Outside)	0'/6' 11"(0m/2.1m)	0'/6' 11"(0m/2.1m)
Tilt Rating (Front to Back/Side to Side)	3°/1.5°	3°/1.5°
Tire Size/Type	15x5"(380x125mm)/Solid	15x5"(380x125mm)/Solid
Power		
Batteries	4x6 V, 220 Ah	4x6 V, 220 Ah
Power Source	24V DC	24V DC
Drive Mode	Motor, Front Wheel	Motor, Front Wheel
Charger Input	100~240V AC	100~240V AC
Charger Output	30A	30A
Hydraulic Tank Capacity	3.9 gal (US)(15L)	3.9 gal (US)(15L)
Weight		
Weight	4,608 lbs(2,090kg)	4,994 lbs(2,265kg)

