

Tape (1/2IN x 119FT PTFE)

SKU: 70885

Description:

Blue Monster is not too thick and not too thin. It was developed by Mill-Rose in response to the demand for a higher-quality PTFE sealing tape that is easier to apply. It's rugged and has not been stretched during the manufacturing process, so it is thicker and creates a more effective seal with less tape, and no need for pipe dope.

Blue Monster thread sealing tape is manufactured from PTFE resin, a polymer consisting of recurring tetrafluoroethylene monomers whose formula is $(CF_2-CF_2)_n$. It is inert and compatible with a very wide range of materials. Use Blue Monster on threads made from galvanized steel, iron, brass, copper, aluminum, stainless steel, polyethylene, polypropylene, PVC, CPVC, ABS, fiberglass and more.

Specifications:

- 99.6% PTFE < 0.4%
- Pigment Color: Blue
- Length: 1429"
- Thickness: 0.0035" +/- 10%
- Density 0.8g/cm³
- Elongation: >100%
- Tensile Strength: 15N/ mm²

Features:

- Compatible w/ a broad range of gasses, liquids and piping materials (will not harden or crack on the joints).
- Effective across a broad range of temperatures and pressures
- Acts as a thread lubricant and anti-seize
- Prevents electrolytic corrosion of threads
- No curing time
- Unlimited shelf life
- Non-flammable and non-toxic

Blue Monster 70886 Thread Seal Tape (3/4IN x 119FT PTFE)

SKU: 70886

Description

—

Blue Monster is not too thick and not too thin. It was developed by Mill-Rose in response to the demand for a higher-quality PTFE sealing tape that is easier to apply. It's rugged and has not been stretched during the manufacturing process, so it is thicker and creates a more effective seal with less tape, and no need for pipe dope.

Blue Monster thread sealing tape is manufactured from PTFE resin, a polymer consisting of recurring tetrafluoroethylene monomers whose formula is $(CF_2-CF_2)_n$. It is inert and compatible with a very wide range of materials. Use Blue Monster on threads made from galvanized steel, iron, brass, copper, aluminum, stainless steel, polyethylene, polypropylene, PVC, CPVC, ABS, fiberglass and more.

Specifications:

- 99.6% PTFE < 0.4%
- Pigment Color: Blue
- Length: 1429"
- Thickness: 0.0035" +/- 10%
- Density 0.8g/cm³
- Elongation: >100%
- Tensile Strength: 15N/ mm²
- Temperature Range: -450°F to +500°F

Features:

- Compatible w/ a broad range of gasses, liquids and piping materials (will not harden or crack on the joints).
- Effective across a broad range of temperatures and pressures
- Acts as a thread lubricant and anti-seize
- Prevents electrolytic corrosion of threads
- No curing time
- Unlimited shelf life
- Non-flammable and non-toxic