

MATERIAL & STYLE

Polyolefin Blend
Straight Wall

1324-12

ANSI/SCTE-77, Tier 15
19.2 lbs

ANSI/SCTE-77, Tier 22
22 lbs

1324-18

ANSI/SCTE-77, Tier 15
25.9 lbs

ANSI/SCTE-77, Tier 22
30 lbs

1324-24

ANSI/SCTE-77, Tier 15
Available Soon

ANSI/SCTE-77, Tier 22
Available Soon

	A	B	C
1324-12	16 1/2	26	12
1324-18	16 1/2	26	18
1324-24	Available soon		



MEDIUM DUTY
ANSI/SCTE TIER 15



HEAVY DUTY
ANSI/SCTE TIER 22

Cover comes standard with permanent markings for manufacturer, load rating, model size and manufacturing location.
*Based upon lid and body combination, this unit can be Tier 15 or Tier 22. T22 rating when paired with T22 polymer concrete lid.

For use in non-vehicular traffic situations only. Weights and dimensions may vary slightly. Actual load rating is determined by the box and cover combination.




OPTIONS

Available Covers: • Polymer Concrete, Flush Solid



Fasteners: • Hex Head Coil Thread Bolt
• Penta Head Coil Thread Bolt



Detail: Bolt Down



Add On Options: • Logos and Special Markings • Rack Mount / Cable Rack • Pulling Eye
• Marking Plate • Cable Arms • Ground Buss
• EMS Marker • Unistrut • Dividers

RAW MATERIAL SPECIFICATION

BODY : Material Property	Test Method	Typical Value ¹
Density	ASTM D1505	0.960 to 0.980, g/cm ³
Tensile Strength, at break	ASTM D638	5,500 to 7,700 psi
Flexural Modulus	ASTM D790	400,000 to 500,000 psi
Impact Resistance	ASTM D5420	60.0 in-lb

¹ The values listed for physical property measurements are nominal values only. Certain physical property measurements are subject to variations consistent with the test methods and are within a generally accepted range for such values.

! WARNING: Cancer - www.P65Warnings.ca.gov

All information contained on this sheet is current at the time of publication. Oldcastle reserves the right to discontinue or update product information without notice.

Revision 02/03/19
© 2019 Oldcastle Infrastructure, Inc