



SILICONE PROJECTS

100% SILICONE ROOF COATING SYSTEM

STEP 1: Clean the roof surface with **115 Cleaner** and lightly pressure wash

STEP 2: Identify if **Primer** is needed; adhesion test required for single-ply and metal substrates

STEP 3: Prep seams, joints, laps, protrusions & fasteners with **100% Silicone Sealant** or **Seal-Fast® Liqui-Flash**.

STEP 4: Apply **100% Silicone Roof Coating** with roller or sprayer at specified rate

SILICONE CLEANER

- 115 Cleaner (16MHA1155)



SILICONE PRIMER

- Multibase SB (16MHMBSB5)
- A-125 Metal Roof Primer (16MHA1255)
- Si TPO Primer (16MHSITPR5)



SILICONE SEALANT

- 100% Silicone Sealant (16MHMBSB5)

Only up to 10 year spec.

- Seal-Fast® Liqui-Flash (16MHLFWH35)

Required for 15 and 20 year spec.



SILICONE COATING

- 100% Silicone Roof Coating (16MHSIRC5)



Colors available:



White



Black



Gray



Tan



Green



Charleston
Green



Brown



Terra Cotta



Safety
Yellow



Tinnors Red



Safety Red

The information herein should not be considered all-inclusive and should always be accompanied by a review of the Mule-Hide specifications and guidelines and good application practices. Statements concerning possible use of Mule-Hide products are made without knowledge of your particular roof and such an application may not be fit for your particular purpose. Visit the Mule-Hide website at www.mulehide.com prior to any installation for updated technical specifications and details.