

## ***"Thunder Series" ITSP-PMPOE Digital Camera***

---

- **Higher Performance** Than Traditional POE Cameras
  - Camera capable of 1,000 ft cable distance
  - 2 MPixel (6 MPixel coming soon)
  - Rated to 140 mph wind speed.
  - Superior Reliability
    - ISO9001:2000 Certification
    - Exceeds NEMA TS2 Cabinet Specifications
    - 2 Year Warranty
  - Lowest Weight: 2 lbs



The ITS Plus POE 2 Mega Pixel camera with a NEMA4 enclosure is optimized for operation with the Thunder Series of AI Processors. Quick disconnect internal Ethernet plug and no nuts or bolts to tighten to adjust camera angle ensures minimal time spent in a bucket truck.

<u>Part Number</u>	<u>Description</u>
ITSP-PMPOE	ITS Plus Pole Mount 2 Mega Pixel POE Camera Warranty: 2 years

### **Camera Specifications**

- Sony based Digital CMOS 1080P/30 fps
- H.264 MJPEG
- Ethernet 10/100 Base-T
- 1/3 inch 2.1 Mega Pixel CMOS
- 0.05 Lux Min at Night to Over 10,000 Lux Daytime
- S/N Ratio greater than 50 dB
- AGC = 12 - 60dB
- Automatic Electronic Shutter 1/30 to 1/30,000 sec
- Power Consumption = 2.1W Typical, 3.0W Max at 12VDC
- Operating Temperature: -40C to 74C
- Meets FCC Part 15, Subpart B
- Effective Pixel: 1,945H, 1,097V

**ITS Plus Products are Designed and Manufactured in the USA**