

ADVERTISEMENT FOR BID FOR A

2025 INTERNATIONAL MODEL HV507 Truck or Equivalent

DEADLINE DATE: FRIDAY, FEBRUARY 14, 2025 AT 10:00 P.M.

The Town of Jean Lafitte is accepting sealed bids for a 2025 International Model HV507 Truck or equivalent.

Bids will be received at the Leo Kerner Multipurpose Complex located at 4917 City Park Drive, Lafitte, LA or on-line at www.centralauctionhouse.com, until Friday, February 14, 2025 at 10:00 a.m. and then at said location and time publicly open and read aloud. Bids can also be emailed to ycrain@townofjeanlafitte.com. Any bid received after the specified time and date will not be considered.

For additional information contact: Yvette Crain at (physical address 4917 City Park Drive) or mailing address at 2654 Jean Lafitte Blvd., Lafitte, LA 70067 or ycrain@townofjeanlafitte.com. (504) 689-2208 or on-line at www.centralauctionhouse.com.

Bids must be submitted on LOUISIANA UNIFORM PUBLIC WORK BID FORM

ALL WRITTEN BIDS, UNLESS OTHERWISE PROVIDED FOR, MUST BE SUBMITTED ON, AND IN ACCORDANCE WITH, FORMS PROVIDED AND PROPERLY SIGNED.

BIDS SUBMITTED IN THE FOLLOWING MANNER WILL NOT BE ACCEPTED:

A. BID SUBMITTED ON PAPER CONTAINS NO SIGNATURE INDICATING INTENT TO BE BOUND.

B. BID FILLED OUT IN PENCIL.

The town reserves the right to reject any or all bids for just cause. Such actions will be in accordance with Title 38 of the L.R.S.

In accordance with L.R.S 38:2212.B(1), the provisions and requirements stated in the bidding documents shall not be considered as informalities and shall not be waived.

Any person with disabilities requiring special accommodation must contact the town no later than seven (7) days prior to bid opening.

DATES PUBLISHED:

Wednesday, January 29, 2025

Wednesday, February 5, 2025

LOUISIANA UNIFORM PUBLIC WORK BID FORM

TO: ITA Truck Sales and Service, LLC
301 Hord St
Harahan, LA 70123
(Owner to provide name and address of owner)

BID FOR: 2025 International Model HV507 truck
Town of Jean Lafitte
Bid # 98210564
(Owner to provide name of project and other identifying information)

The undersigned bidder hereby declares and represents that she/he: a) has carefully examined and understands the Bidding Documents, b) has not received, relied on, or based his bid on any verbal instructions contrary to the Bidding Documents or any addenda, c) has personally inspected and is familiar with the project site, and hereby proposes to provide all labor, materials, tools, appliances and facilities as required to perform, in a workmanlike manner, all work and services for the construction and completion of the referenced project, all in strict accordance with the Bidding Documents prepared by: Chris Ormond
and dated: 01/29/2025
(Owner to provide name of entity preparing bidding documents.)

Bidders must acknowledge all addenda. The Bidder acknowledges receipt of the following **ADDENDA:** (Enter the number the Designer has assigned to each of the addenda that the Bidder is acknowledging) N/A.

TOTAL BASE BID: For all work required by the Bidding Documents (including any and all unit prices designated "Base Bid" * but not alternates) the sum of:

One Hundred Twenty Six thousand Eight Hundred Fifty dollars and eighty two cents Dollars (\$ 126,850.82)

ALTERNATES: For any and all work required by the Bidding Documents for Alternates including any and all unit prices designated as alternates in the unit price description.

Alternate No. 1 *(Owner to provide description of alternate and state whether add or deduct)* for the lump sum of:
Dollars (\$ _____)

Alternate No. 2 *(Owner to provide description of alternate and state whether add or deduct)* for the lump sum of:
Dollars (\$ _____)

Alternate No. 3 *(Owner to provide description of alternate and state whether add or deduct)* for the lump sum of:
Dollars (\$ _____)

NAME OF BIDDER: ITA Truck Sales and Service, LLC

ADDRESS OF BIDDER: 301 Hord St
Harahan, LA 70123

LOUISIANA CONTRACTOR'S LICENSE NUMBER: N-2023-00131

NAME OF AUTHORIZED SIGNATORY OF BIDDER: Chris Ormond

TITLE OF AUTHORIZED SIGNATORY OF BIDDER: Sales Account Manager

SIGNATURE OF AUTHORIZED SIGNATORY OF BIDDER **: Chris Ormond

DATE: 01/29/2025

THE FOLLOWING ITEMS ARE TO BE INCLUDED WITH THE SUBMISSION OF THIS LOUISIANA UNIFORM PUBLIC WORK BID FORM:

* The Unit Price Form shall be used if the contract includes unit prices. Otherwise it is not required and need not be included with the form. The number of unit prices that may be included is not limited and additional sheets may be included if needed.

** A **CORPORATE RESOLUTION OR WRITTEN EVIDENCE** of the authority of the person signing the bid for the public work as prescribed by LA R.S. 38:2212(B)(5).

BID SECURITY in the form of a bid bond, certified check or cashier's check as prescribed by LA R.S. 38:2218(A) attached to and made a part of this bid.

LOUISIANA UNIFORM PUBLIC WORK BID FORM
UNIT PRICE FORM

TO:

ITA Truck Sales and Service, LLC
301 Hord St
Harahan, LA 70123

BID FOR:

2026 International Model HV507 truck
Town of Jean Lafitte
Bid # 98210564

(Owner to provide name and address of owner)

(Owner to provide name of project and other identifying information)

UNIT PRICES: This form shall be used for any and all work required by the Bidding Documents and described as unit prices. Amounts shall be stated in figures and only in figures.

DESCRIPTION:	<input checked="" type="checkbox"/> Base Bid or <input type="checkbox"/> Alt.#				
REF. NO.	QUANTITY:	UNIT OF MEASURE:	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)	
	1	ea	\$126,850.82	\$126,850.82	
DESCRIPTION:	<input type="checkbox"/> Base Bid or <input type="checkbox"/> Alt.#				
REF. NO.	QUANTITY:	UNIT OF MEASURE:	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)	
DESCRIPTION:	<input type="checkbox"/> Base Bid or <input type="checkbox"/> Alt.#				
REF. NO.	QUANTITY:	UNIT OF MEASURE:	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)	
DESCRIPTION:	<input type="checkbox"/> Base Bid or <input type="checkbox"/> Alt.#				
REF. NO.	QUANTITY:	UNIT OF MEASURE:	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)	
DESCRIPTION:	<input type="checkbox"/> Base Bid or <input type="checkbox"/> Alt.#				
REF. NO.	QUANTITY:	UNIT OF MEASURE:	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)	
DESCRIPTION:	<input type="checkbox"/> Base Bid or <input type="checkbox"/> Alt.#				
REF. NO.	QUANTITY:	UNIT OF MEASURE:	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)	
DESCRIPTION:	<input type="checkbox"/> Base Bid or <input type="checkbox"/> Alt.#				
REF. NO.	QUANTITY:	UNIT OF MEASURE:	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)	
DESCRIPTION:	<input type="checkbox"/> Base Bid or <input type="checkbox"/> Alt.#				
REF. NO.	QUANTITY:	UNIT OF MEASURE:	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)	
DESCRIPTION:	<input type="checkbox"/> Base Bid or <input type="checkbox"/> Alt.#				
REF. NO.	QUANTITY:	UNIT OF MEASURE:	UNIT PRICE	UNIT PRICE EXTENSION (Quantity times Unit Price)	

Wording for "DESCRIPTION" is to be provided by the Owner.
All quantities are estimated. The contractor will be paid based upon actual quantities as verified by the Owner.

License No. N'-2023-00379

2023-2025

Not Transferable


Louisiana Motor Vehicle Commission

This Certifies that
Chris Ormond of Metairie, LA
has been licensed by this Commission as a
MOTOR VEHICLE SALESMAN,
Employed by Motor Vehicle Dealer Licensee
N -2023-00131
iTA Truck Sales & Service, L.L.C.
301 Hord Street
Harahan, LA 70123

pursuant to the laws of the State of Louisiana for the period ending April 30, 2025.

Louisiana Motor Vehicle Commission

Dated May 1, 2023



Executive Director

NOTE: This Certificate is to be retained by the Employer.
It is to be returned by the Employer to the Commission
Office at 3017 Kingman Street, Metairie, LA 70006, within
ten days of the termination of the Salesman's employment.


Termination Date:



CERTIFICATE OF AUTHORITY

The undersigned, the Certifying Officer of iTA Truck Sales & Service, L.L.C., a Louisiana limited liability company (the "**Company**"), hereby declares that:

1. The undersigned, Christopher D. Schouest is the President of the Company and is named in the Articles of Organization of the Company filed with the Louisiana Secretary of State as having authority to certify the membership of any member, the authenticity of any records of the Company, or the authority of any person to act on behalf of the Company.
2. The undersigned certifies that:
 - (a) Christopher Ormond is an Sales Account Manager for the Company and in such capacity performs Municipal Sales for the Company and is duly authorized by the Company to execute and deliver on behalf of the Company any and all documents, contracts or amendments, he deems necessary or appropriate with respect to any transaction between the Company and any State or Municipal Government entity in the State of Louisiana, including without limitation any transaction between the Company and the City of New Orleans.
 - (b) The foregoing authority is in full force and effect and has not been revoked or rescinded.

By: 
Christopher D. Schouest
President and Certifying Officer
iTA Truck Sales & Service, L.L.C.

Date: April 11, 2022

In Witness Whereof, I hereby set my hand this 11th day of April, 2022



Noreen Arcides

Notary Number: 45403

My Commission Expires: At Death



NOREEN ARCIDES
Notary Public
Notary ID No. 45403
Lafayette Parish, Louisiana

2025 INTERNATIONAL MODEL HV507 Truck or equivalent

Dimensions/Features

DIMENSION: Wheelbase (WB): 240.00, CA: 121.10, Axle to Frame: 96.00

ENGINE, DIESEL: {Cummins B6.7 280} EPA 2024, 280HP @ 2400 RPM, 660 lb-ft Torque @ 1600 RPM, 2600 RPM Governed Speed, 280 Peak HP (Max)

TRANSMISSION, AUTOMATIC: {Allison 2500 RDS} 6th Generation Controls, Wide Ratio, 5-Speed with Overdrive, with PTO Provision, Less Retarder, with 33,000-lb GVW and GCW Max, On/Off Highway

CLUTCH: Omit Item (Clutch & Control)

AXLE, FRONT DRIVING: {Meritor MX-14-120 EVO} Single Reduction, 14,000-lb Capacity, with Hub Piloted Wheel Mounting

AXLE, REAR, SINGLE: {Dana Spicer S23-190} Single Reduction, Hypoid Gearing, 23,000-lb Capacity, R Wheel Ends Gear Ratio(s): 6.14

CAB: Conventional 6-Man Crew Cab

TIRE, FRONT: (2) 11R24.5 Load Range H HSR 3 (CONTINENTAL), 473 rev/mile, 75 MPH, All-Position

TIRE, REAR: (4) 11R24.5 Load Range H HDL2 DL+ (CONTINENTAL), 468 rev/mile, 75 MPH, Drive

SUSPENSION, REAR, SINGLE: 20,000-lb Capacity, Vari-Rate Springs, with 4500-lb Capacity Auxiliary Rubber Springs

Vehicle Specification

HV50700 Base Chassis, Model HV507 SFA 240.00 Wheelbase, 121.10 CA, and 96.00 Axle to Frame. 0001570 TOW HOOK, FRONT (2) Frame Mounted

0001572 TOW HOOK, REAR (2)

0001ANB AXLE CONFIGURATION 4x4

0001CAG FRAME RAILS Heat Treated Alloy Steel (120,000 PSI Yield); 10.250" x 3.610" x 0.375" (260.4mm x 91.7mm x 9.5mm); 456.0" (11582mm) Maximum OAL

0001LEH LICENSE PLATE HOLDER Single Plate, Swing Type, Mounted Below Front Bumper

0001LLA BUMPER, FRONT Swept Back, Steel, Heavy Duty

0001MEJ FRAME DIMPLE Dimple on Left and Right Top Flange of Frame Rail to Reference Rear Axle Centerline

0001SAL CROSSMEMBER, REAR, AF (1)

0001WDS FRAME EXTENSION, FRONT Integral; 20" In Front of Grille

0001WGH WHEELBASE RANGE 207" (525cm) Through and Including 254" (645cm)

0002GAE AXLE, FRONT DRIVING {Meritor MX-14-120 EVO} Single Reduction, 14,000-lb Capacity, with Hub Piloted Wheel Mounting

0002WLC AXLE, FRONT DRIVING, LUBE {EmGard FE-75W-90} Synthetic Oil; 1 thru 29.99 Pints

0003ADD SUSPENSION, FRONT, SPRING Parabolic Taper Leaf, Shackle Type, 14,000-lb Capacity, with Shock Absorbers

0004091 BRAKE SYSTEM, AIR Dual System for Straight Truck Applications

0004722 DRAIN VALVE {Bendix DV-2} Automatic, with Heater, for Air Tank

0004AZA AIR BRAKE ABS {Bendix AntiLock Brake System} 4-Channel (4 Sensor/4 Modulator) Full Vehicle Wheel Control System

0004EBS AIR DRYER {Bendix AD-9} with Heater

0004ETD BRAKE CHAMBERS, FRONT AXLE {MGM} 20 SqIn

0004EXU BRAKE CHAMBERS, REAR AXLE {Bendix EverSure} 30/30 SqIn Spring Brake

0004GBM BRAKE, PARKING Manual Push-Pull Pneumatic Parking Brake

0004LAA SLACK ADJUSTERS, FRONT {Haldex} Automatic

0004LGA SLACK ADJUSTERS, REAR {Haldex} Automatic

0004RUJ AIR SUPPLY, AUXILIARY on Air Reservoir with Glad Hand Connector

0004SPA AIR COMPRESSOR {Cummins} 18.7 CFM

0004VDU AIR TANK LOCATION (2) Mounted Left Side BOC Under Battery Box

0004VGG AIR DRYER LOCATION Mounted Inside Left Rail, Behind Transfer Case Mounting

0004WBX DUST SHIELDS, FRONT BRAKE for Air Cam Brakes

0004WDM DUST SHIELDS, REAR BRAKE for Air Cam Brakes

0004XDP BRAKES, FRONT {Meritor 16.5X5 Q-PLUS CAST} Air S-Cam Type, Cast Spider, Fabricated Shoe, Double Anchor Pin, Size 16.5" X 5", 14,700-lb Capacity

0004XDR BRAKES, REAR {Meritor 16.5X7 Q-PLUS CAST} Air S-Cam Type, Cast Spider, Fabricated Shoe, Double Anchor Pin, Size 16.5" X 7", 23,000-lb Capacity per Axle

0005710 STEERING COLUMN Tilting and Telescoping 0005CAW STEERING WHEEL 4-Spoke; 18" Dia., Black

0005PSL STEERING GEAR {Sheppard M110} Power

0006DHK DRIVELINE SYSTEM {Dana Spicer} SPL170 Main Driveline, 1710 Driveline to Transfer Case, SPL140 Driveline to Front Axle, for 4x4

0007BEU AFTERTREATMENT COVER Aluminum

0007BMA EXHAUST SYSTEM Horizontal Aftertreatment System, Frame Mounted Right Side Under Cab, for Single Vertical Tail Pipe, Frame Mounted Right Side Back of Cab, for All-Wheel Drive

0007SCP ENGINE EXHAUST BRAKE for Cummins ISB/B6.7/ISL/L9 Engine with Variable Vane Turbo Charger

0007WBA TAIL PIPE (1) Turnback Type, Bright

0007WDM EXHAUST HEIGHT 10'

0007WDN MUFFLER/TAIL PIPE GUARD (1) Aluminum

0008000 ELECTRICAL SYSTEM 12-Volt, Standard Equipment

0008GHU ALTERNATOR {Delco Remy 28SI} Brush Type, 12 Volt, 200 Amp Capacity, Pad Mount, with Remote Sense

0008HAE BODY BUILDER WIRING Rear of Frame; Includes Sealed Connectors for Tail/Amber Turn/Marker/ Backup/Accessory Power/Ground and Sealed Connector for Stop/Turn

0008HAH ELECTRIC TRAILER BRAKE/LIGHTS Accommodation Package to Rear of Frame; for Combined Trailer Stop, Tail, Turn, Marker Light Circuits; Includes Electric Trailer Brake Accommodation Package with Cab Connections for Mounting Customer Installed Electric Brake Unit, Less Trailer Socket

0008MSG BATTERY SYSTEM {Fleetrite} Maintenance-Free, (3) 12-Volt 1980CCA Total, Top Threaded Stud

0008RGA 2-WAY RADIO Wiring Effects; Wiring with 20 Amp Fuse Protection, Includes Ignition Wire with 5 Amp Fuse, Wire Ends Heat Shrink and Routed to Center of Header Console in Cab

0008RMZ SPEAKERS (2) 6.5" Dual Cone Mounted in Both Doors, (2) 5.25" Dual Cone Mounted in Both B-Pillars

0008RNB CB RADIO Accommodation Package, Header Mounted, Feeds from Accessory Side of Ignition Switch, Includes Power Source, One Antenna and Antenna Base with Wiring on Left Side Mirror

0008RPB RADIO, STEERING WHEEL CONTROLS Mounted in Steering Wheel, Radio Function Control Switch, Includes Volume Up/Down, Mute, Forward/Back and Bluetooth Answer/Disconnect

0008RPP ANTENNA Shark Fin, Roof Mounted

0008RPS RADIO AM/FM/WB/Clock/Bluetooth/USB Input/Auxiliary Input

0008THB BACK-UP ALARM Electric, 102 dBA

0008TKB STOP, TURN, TAIL & B/U LIGHTS {Truck Lite} Super 44, with LED Lights for Stop, Turn & Tail Lights, Truck Lite Super 40 for Backup Lights, with Power Module, "International" Termination and Less Junction Box, Includes Incandescent License Plate Light

0008TKK TRAILER AUXILIARY FEED CIRCUIT for Electric Trailer Brake Accommodation/Air Trailer ABS; with 30 Amp Fuse and Relay, Controlled by Ignition Switch

0008VAY HORN, ELECTRIC Disc Style

0008WBW JUMP START STUD 12V, Remote Mounted

0008WCK POWER SOURCE, TERMINAL TYPE 2-Post

0008WDB BATTERY BOX Steel, with Plastic Cover, 30" Wide, 2-4 Battery Capacity, Mounted Left Side Back of Fuel Tank

0008WGB SOLENOID, AIR for Customer Use; Provides (2) Normally Closed Pilot Air Source, Approx. 4 CFM, Includes Latched Switch in Cab; Air Available Only with Key in "Ignition" or "Accessory" Position; Air Will Exhaust with Key in "Off" Position

0008WGU BATTERY BOX COVER Aluminum

0008WPH CLEARANCE/MARKER LIGHTS (5) {Truck Lite} Amber LED Lights, Flush Mounted on Cab or Sunshade

0008WPZ TEST EXTERIOR LIGHTS Pre-Trip Inspection will Cycle all Exterior Lamps Except Back-up Lights

0008WRB HEADLIGHTS ON W/WIPERS Headlights Will Automatically Turn On if Windshield Wipers are Turned On

0008WWJ INDICATOR, LOW COOLANT LEVEL with Audible Alarm

0008WXB HEADLIGHT WARNING BUZZER Sounds When Head Light Switch is on and Ignition Switch is in "Off" Position

0008WZP INDICATOR, BATTERY WARNING Green BATTERY ON Indicator, Mounted on Left Side of Instrument Panel, To be Used with Factory Installed or Customer Mounted Battery Disconnect Switch

0008XAH CIRCUIT BREAKERS Manual-Reset (Main Panel) SAE Type III with Trip Indicators, Replaces All Fuses

0008XBK SWITCH, AUXILIARY Switch 40 amp Circuit for Customer Use; Includes Wiring Connection at Power Distribution Center (PDC) and Control in Cab

0008XGT TURN SIGNALS, FRONT Includes LED Side Turn Lights Mounted on Fender

0008XHD BATTERY DISCONNECT SWITCH 300 Amp, Disconnects Charging Circuits, Locks with Padlock, Cab Mounted

0008XHN HORN, AIR Single Trumpet, Black, with Lanyard Pull Cord

0008XKL STARTING MOTOR {Mitsubishi Electric Automotive America 90P47} 12-Volt, with Soft-Start

0008XKM SWITCH, AIR HORN, PASSENGER Fire Truck Application; Momentary Switch Located in Instrument Panel Close to Passenger, Driver Also To Activate Switch with Lanyard

0008XNZ HEADLIGHTS Halogen, with Daytime Running Lights

0008XPK POWER SOURCE, ADDITIONAL Auxiliary Power Outlet (APO) with USB-A Port and USB-C Port, Located in the Instrument Panel

0009585 FENDER EXTENSIONS Rubber

0009AAB LOGOS EXTERIOR Model Badges

0009AAE LOGOS EXTERIOR, ENGINE Badges

0009HAN INSULATION, UNDER HOOD for Sound Abatement

0009HBM GRILLE Stationary, Chrome

0009HBN INSULATION, SPLASH PANELS for Sound Abatement

0009WAC BUG SCREEN Mounted Behind Grille

0009WBC FRONT END Tilting, Fiberglass, with Three Piece Construction, for WorkStar/HV

0010021 CHASSIS COATING Corrosion Resistant E-Coat Primer Coating for Single Frame Rails

0010060 PAINT SCHEMATIC, PT-1 Single Color, Design 100

0010761 PAINT TYPE Base Coat/Clear Coat, 1-2 Tone

0010AGB COMMUNICATIONS MODULE Telematics Device with Over the Air Programming; Includes Five Year Data Plan and International 360

0010BAE LABEL, DEF "DEF ONLY"

0010WCY SAFETY TRIANGLES

0010XAN FIRE EXTINGUISHER 5 lb Class A B C

0010XAP FIRE EXTINGUISHER BRACKET Mounted Left Side Driver Seat

0011001 CLUTCH Omit Item (Clutch & Control)

0012703 ANTI-FREEZE Red, Extended Life Coolant; To -40 Degrees F/ -40 Degrees C, Freeze Protection

0012849 BLOCK HEATER, ENGINE 120V/1000W, for Cummins ISB/B6.7/ISL/L9 Engines

0012EMZ VENDOR WARRANTY, ENGINE {Cummins} B6.7 Engine, 3-Year Unlimited Miles Standard Warranty

0012EXW ENGINE, DIESEL {Cummins B6.7 280} EPA 2024, 280HP @ 2400 RPM, 660 lb-ft Torque @ 1600 RPM, 2600 RPM Governed Speed, 280 Peak HP (Max)

0012THT FAN DRIVE {Horton Drivemaster} Two-Speed Type, Direct Drive, with Residual Torque Device for Disengaged Fan Speed

0012UWZ RADIATOR Aluminum, Cross Flow, Front to Back System, 1228 SqIn, with 1167 SqIn Charge Air Cooler, Includes In- Tank Oil Cooler

0012VBC AIR CLEANER Single Element

0012VJR EMISSION, CALENDAR YEAR {Cummins B6.7} EPA, OBD and GHG Certified for Calendar Year 2024

0012VXT THROTTLE, HAND CONTROL Engine Speed Control; Electronic, Stationary, Variable Speed; Mounted on Steering Wheel

0012VYP ENGINE CONTROL, REMOTE MOUNTED No Provision for Remote Mounted Engine Control

0012WVG EPA IDLE COMPLIANCE Low NOx Idle Engine, Complies with EPA Clean Air Regulations; Includes "Certified Clean Idle" Decal on Hood

0012WZE CARB IDLE COMPLIANCE Does Not Comply with California Clean Air Idle Regulations

0012XCS CARB EMISSION WARR COMPLIANCE Does Not Comply with CARB Emission Warranty

0013BBJ TRANSMISSION, AUTOMATIC {Allison 2500 RDS} 6th Generation Controls, Wide Ratio, 5-Speed with Overdrive, with PTO Provision, Less Retarder, with 33,000-lb GVW and GCW Max, On/Off Highway

0013TKL TRANSFER CASE {Meritor MTC-4208} 2-Speed, 8,300 lb-ft Torque Rating, Less PTO Provision, Electric Over Air Control, with Lube Pump

0013WAW OIL COOLER, TRANSMISSION {Modine} Water to Oil Type 0013WDB TRANSFER CASE LUBE {EmGard 50W} Synthetic; 1 thru 14.99 Pints

0013WGC OIL COOLER, TRANSFER CASE with Oil Coolant Lines Routed to Oil Cooler

0013WLN TRANSMISSION OIL Synthetic; 20 thru 28 Pints

0013WVS TRANSMISSION SHIFT CONTROL T-Handle

0013WVV NEUTRAL AT STOP Allison Transmission Shifts to Neutral When Service Brake is Depressed and Vehicle is at Stop; Remains in Neutral Until Service Brake is Released

0013WYY SHIFT CONTROL PARAMETERS {Allison} 1000 or 2000 Series Transmissions, Performance Programming

0013XAN PTO LOCATION Customer Does Not Intend to Install PTO

0014877 DIFFERENTIAL, LOCKING {Detroit Locker} No-Spin; for Dana Spicer (previously Eaton) Rear Axles

0014AHE AXLE, REAR, SINGLE {Dana Spicer S23-190} Single Reduction, Hypoid Gearing, 23,000-lb Capacity, R Wheel Ends

0014VAG SUSPENSION, REAR, SINGLE 20,000-lb Capacity, Vari-Rate Springs, with 4500-lb Capacity Auxiliary Rubber Springs

0014WMG AXLE, REAR, LUBE {EmGard FE-75W-90} Synthetic Oil; 30 thru 39.99 Pints

0015LMS FUEL/WATER SEPARATOR 12 VDC Electric Heater, Includes Pre-Heater, Includes Water-in-Fuel Sensor, Cummins Supplied on Engine

0015SRE FUEL TANK Top Draw, Non-Polished Aluminum, D-Style, 19" Tank Depth, 50 US Gal (189L), Mounted Left Side, Under Cab

0015WDG DEF TANK 7 US Gal (26L) Capacity, Frame Mounted Outside Left Rail, Under Cab

0016196 CAB Conventional 6-Man Crew Cab

0016ATC AUTOMATIC CLIMATE CONTROL Automatically Maintains Cabin Comfort Based on Selected Temperature

0016BAM AIR CONDITIONER with Integral Heater and Defroster

0016GED GAUGE CLUSTER Base Level; English with English Electronic Speedometer

0016HCS GAUGE, TEMPERATURE, AMBIENT Sensor Wiring with Display Unit Mounted in Cluster

0016HGH GAUGE, OIL TEMP, AUTO TRANS for Allison Transmission

0016HGL GAUGE, OIL TEMP, REAR AXLE

0016HHE GAUGE, AIR CLEANER RESTRICTION {Filter-Minder} Mounted in Instrument Panel

0016HKT IP CLUSTER DISPLAY On Board Diagnostics Display of Fault Codes in Gauge Cluster

0016JNT SEAT, DRIVER {National 2000} Air Suspension, High Back with Integral Headrest, Vinyl, Isolator, 1 Chamber Lumbar, with 2 Position Front Cushion Adjust, -3 to +14 Degree Angle Back Adjust

0016LUM SEAT, PASSENGER {National} Non-Suspension, High Back with Integral Headrest, Vinyl, with Fixed Back, with Under Seat Storage

0016SDC GRAB HANDLE, EXTERIOR (2) Chrome, Towel Bar Type, with Anti-Slip Rubber Inserts, for Cab Entry Mounted Left and Right Side at B-Pillar

0016SDZ MIRROR, CONVEX, HOOD MOUNTED {Lang Mekra} (2) Right and Left Side, Bright, 7.5" Sq.

0016SMT SEAT, REAR {National} BENCH; Full Width; Vinyl, with Fixed Back and Two Integral Outboard Headrests

0016SNV MIRRORS (2) Aero Pedestal, Power Adjust, Heated, Turn Signals, Bright Heads, Black Arms, 6.5" x 14" Flat Glass, Includes 6.5" x 6" Convex Mirrors, for 102" Load Width

0016VCB SEAT BELT All Orange; 4 to 6

0016VKD CAB INTERIOR TRIM Classic, for Crew Cab 0016VLV MONITOR, TIRE PRESSURE Omit

0016WBY ARM REST, RIGHT, DRIVER SEAT

0016WEE CAB SOUND INSULATION Includes Dash Insulator and Engine Cover Insulator

0016WHJ HOSE CLAMPS, HEATER HOSE {Breeze} Belleville Washer Type

0016WJV WINDOW, POWER (4) And Power Door Locks, Front and Rear Doors, Left and Right, Includes Express Down Feature

0016WLS FRESH AIR FILTER Attached to Air Intake Cover on Cowl Tray in Front of Windshield Under Hood

0016WSK CAB REAR SUSPENSION Air Bag Type

0016XCW CAB, INTERIOR TRIM, CLOSEOUT Under IP, Driver Side

0016XJN INSTRUMENT PANEL Flat Panel

0016ZHY ACCESS, CAB Aluminum, Self-Cleaning, Open and Serrated Design, Driver & Passenger Sides, Two Steps per Door, for use with Crew Cab

0016ZPH FLOOR, COATING LINE-X, Applied to Interior Cab Floor

0026DWJ WHEEL, SPARE, DISC {Accuride 42362} 24.5x8.25 Rims, Standard Polish Aluminum, 10-Stud, 285.75mm BC, Hub- Piloted

0027DWJ WHEELS, FRONT {Accuride 42362} DISC; 24.5x8.25 Rims, Standard Polish Aluminum, 10-Stud, 285.75mm BC, Hub- Piloted, Flanged Nut, with Steel Hubs

0028DWJ WHEELS, REAR {Accuride 42362} DUAL DISC; 24.5x8.25 Rims, Standard Polish Aluminum, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs

07384225439 (2) TIRE, FRONT 11R24.5 Load Range H HSR 3 (CONTINENTAL), 473 rev/mile, 75 MPH, All-Position

07384225447 (4) TIRE, REAR 11R24.5 Load Range H HDL2 DL+ (CONTINENTAL), 468 rev/mile, 75 MPH, Drive

0040128 WARRANTY Standard for HV507, HV50B, HV607 Models, Effective with Vehicles Built July 1, 2017 or Later, CTS-2025A

Prepared For:
JEAN LAFITTE
CHRIS COLLIER
1233 Westbank Expy
Harvey, LA 70058-4462
(504)832 - 2516
Reference ID: Jean Lafitte

Presented By:
ITA-NOLA, LLC
Chris Ormond
301 HORD
HARAHAN LA 70123 -
(504)733-7711

Thank you for the opportunity to provide you with the following quotation on a new International truck. I am sure the following detailed specification will meet your operational requirements, and I look forward to serving your business needs.

Model Profile
2023 HV507 SFA (HV507)

AXLE CONFIG:	4X4
APPLICATION:	Stake Flat
MISSION:	Requested GVWR: 33000. Calc. GVWR: 33000. Calc. GCWR: 33000 Calc. Start / Grade Ability: 24.92% / 2.27% @ 55 MPH Calc. Geared Speed: 73.4 MPH
DIMENSION:	Wheelbase: 240.00, CA: 121.10, Axle to Frame: 96.00
ENGINE, DIESEL:	{Cummins B6.7 280} EPA 2024, 280HP @ 2400 RPM, 660 lb-ft Torque @ 1600 RPM, 2600 RPM Governed Speed, 280 Peak HP (Max)
TRANSMISSION, AUTOMATIC:	{Allison 2500 RDS} 6th Generation Controls, Wide Ratio, 5-Speed with Overdrive, with PTO Provision, Less Retarder, with 33,000-lb GVW and GCW Max, On/Off Highway
CLUTCH:	Omit Item (Clutch & Control)
AXLE, FRONT DRIVING:	{Meritor MX-14-120 EVO} Single Reduction, 14,000-lb Capacity, with Hub Piloted Wheel Mounting
AXLE, REAR, SINGLE:	{Dana Spicer S23-190} Single Reduction, Hypoid Gearing, 23,000-lb Capacity, R Wheel Ends Gear Ratio: 6.14
CAB:	Conventional 6-Man Crew Cab
TIRE, FRONT:	(2) 11R24.5 Load Range H HSR 3 (CONTINENTAL), 473 rev/mile, 75 MPH, All-Position
TIRE, REAR:	(4) 11R24.5 Load Range H HDL2 DL+ (CONTINENTAL), 468 rev/mile, 75 MPH, Drive
SUSPENSION, REAR, SINGLE:	20,000-lb Capacity, Vari-Rate Springs, with 4500-lb Capacity Auxiliary Rubber Springs
PAINT:	Cab schematic 100WK Location 1: 9219, Winter White (Std) Chassis schematic N/A

<u>Code</u>	<u>Description</u>
HV50700	Base Chassis, Model HV507 SFA with 240.00 Wheelbase, 121.10 CA, and 96.00 Axle to Frame.
1570	TOW HOOK, FRONT (2) Frame Mounted
1572	TOW HOOK, REAR (2)
1ANB	AXLE CONFIGURATION 4x4
	<u>Notes</u> : Pricing may change if axle configuration is changed.
1CAG	FRAME RAILS Heat Treated Alloy Steel (120,000 PSI Yield); 10.250" x 3.610" x 0.375" (260.4mm x 91.7mm x 9.5mm); 456.0" (11582mm) Maximum OAL
1LEH	LICENSE PLATE HOLDER Single Plate, Swing Type, Mounted Below Front Bumper
1LLA	BUMPER, FRONT Swept Back, Steel, Heavy Duty
1MEJ	FRAME DIMPLE Dimple on Left and Right Top Flange of Frame Rail to Reference Rear Axle Centerline
1SAL	CROSSMEMBER, REAR, AF (1)
1WDS	FRAME EXTENSION, FRONT Integral; 20" In Front of Grille
1WGH	WHEELBASE RANGE 207" (525cm) Through and Including 254" (645cm)
2GAE	AXLE, FRONT DRIVING {Meritor MX-14-120 EVO} Single Reduction, 14,000-lb Capacity, with Hub Piloted Wheel Mounting
	<u>Notes</u> : Axle Lead Time is 90 Days
2WLC	AXLE, FRONT DRIVING, LUBE {EmGard FE-75W-90} Synthetic Oil; 1 thru 29.99 Pints
3ADD	SUSPENSION, FRONT, SPRING Parabolic Taper Leaf, Shackle Type, 14,000-lb Capacity, with Shock Absorbers
4091	BRAKE SYSTEM, AIR Dual System for Straight Truck Applications
	<u>Includes</u> : BRAKE LINES Color and Size Coded Nylon : DRAIN VALVE Twist-Type : GAUGE, AIR PRESSURE (2) Air 1 and Air 2 Gauges; Located in Instrument Cluster : PARKING BRAKE CONTROL Yellow Knob, Located on Instrument Panel : PARKING BRAKE VALVE For Truck : QUICK RELEASE VALVE On Rear Axle for Spring Brake Release: 1 for 4x2, 2 for 6x4 : SPRING BRAKE MODULATOR VALVE R-7 for 4x2, SR-7 with relay valve for 6x4/8x6
4722	DRAIN VALVE {Bendix DV-2} Automatic, with Heater, for Air Tank
4AZA	AIR BRAKE ABS {Bendix AntiLock Brake System} 4-Channel (4 Sensor/4 Modulator) Full Vehicle Wheel Control System
4EBS	AIR DRYER {Bendix AD-9} with Heater
4ETD	BRAKE CHAMBERS, FRONT AXLE {MGM} 20 SqIn
4EXU	BRAKE CHAMBERS, REAR AXLE {Bendix EverSure} 30/30 SqIn Spring Brake
4GBM	BRAKE, PARKING Manual Push-Pull Pneumatic Parking Brake
4LAA	SLACK ADJUSTERS, FRONT {Haldex} Automatic
4LGA	SLACK ADJUSTERS, REAR {Haldex} Automatic
4RUJ	AIR SUPPLY, AUXILIARY on Air Reservoir with Glad Hand Connector

<u>Code</u>	<u>Description</u>
4SPA	AIR COMPRESSOR {Cummins} 18.7 CFM
4VDU	AIR TANK LOCATION (2) Mounted Left Side BOC Under Battery Box
4VGG	AIR DRYER LOCATION Mounted Inside Left Rail, Behind Transfer Case Mounting
4WBX	DUST SHIELDS, FRONT BRAKE for Air Cam Brakes
4WDM	DUST SHIELDS, REAR BRAKE for Air Cam Brakes
4XDP	BRAKES, FRONT {Meritor 16.5X5 Q-PLUS CAST} Air S-Cam Type, Cast Spider, Fabricated Shoe, Double Anchor Pin, Size 16.5" X 5", 14,700-lb Capacity
4XDR	BRAKES, REAR {Meritor 16.5X7 Q-PLUS CAST} Air S-Cam Type, Cast Spider, Fabricated Shoe, Double Anchor Pin, Size 16.5" X 7", 23,000-lb Capacity per Axle
5710	STEERING COLUMN Tilting and Telescoping
5CAW	STEERING WHEEL 4-Spoke; 18" Dia., Black
5PSL	STEERING GEAR {Sheppard M110} Power
6DHK	DRIVELINE SYSTEM {Dana Spicer} SPL170 Main Driveline, 1710 Driveline to Transfer Case, SPL140 Driveline to Front Axle, for 4x4
7BEU	AFTERTREATMENT COVER Aluminum
7BMA	EXHAUST SYSTEM Horizontal Aftertreatment System, Frame Mounted Right Side Under Cab, for Single Vertical Tail Pipe, Frame Mounted Right Side Back of Cab, for All-Wheel Drive
7SCP	ENGINE EXHAUST BRAKE for Cummins ISB/B6.7/ISL/L9 Engine with Variable Vane Turbo Charger
7WBA	TAIL PIPE (1) Turnback Type, Bright
7WDM	EXHAUST HEIGHT 10'
7WDN	MUFFLER/TAIL PIPE GUARD (1) Aluminum
8000	ELECTRICAL SYSTEM 12-Volt, Standard Equipment
	<u>Includes</u>
	: DATA LINK CONNECTOR For Vehicle Programming and Diagnostics In Cab
	: HAZARD SWITCH Push On/Push Off, Located on Instrument Panel to Right of Steering Wheel
	: HEADLIGHT DIMMER SWITCH Integral with Turn Signal Lever
	: PARKING LIGHT Integral with Front Turn Signal and Rear Tail Light
	: STARTER SWITCH Electric, Key Operated
	: STOP, TURN, TAIL & B/U LIGHTS Dual, Rear, Combination with Reflector
	: TURN SIGNAL SWITCH Self-Cancelling for Trucks, Manual Cancelling for Tractors, with Lane Change Feature
	: WINDSHIELD WIPER SWITCH 2-Speed with Wash and Intermittent Feature (5 Pre-Set Delays), Integral with Turn Signal Lever
	: WINDSHIELD WIPERS Single Motor, Electric, Cowl Mounted
	: WIRING, CHASSIS Color Coded and Continuously Numbered
8GHU	ALTERNATOR {Delco Remy 28SI} Brush Type, 12 Volt, 200 Amp Capacity, Pad Mount, with Remote Sense
8HAE	BODY BUILDER WIRING Rear of Frame; Includes Sealed Connectors for Tail/Amber Turn/Marker/ Backup/ Accessory Power/Ground and Sealed Connector for Stop/Turn
8HAH	ELECTRIC TRAILER BRAKE/LIGHTS Accommodation Package to Rear of Frame; for Combined Trailer Stop, Tail, Turn, Marker Light Circuits; Includes Electric Trailer Brake Accommodation Package with Cab Connections for Mounting Customer Installed Electric Brake Unit, Less Trailer Socket
8MSG	BATTERY SYSTEM {Fleetrite} Maintenance-Free, (3) 12-Volt 1980CCA Total, Top Threaded Stud

<u>Code</u>	<u>Description</u>
8RGA	2-WAY RADIO Wiring Effects; Wiring with 20 Amp Fuse Protection, Includes Ignition Wire with 5 Amp Fuse, Wire Ends Heat Shrink and Routed to Center of Header Console in Cab
8RMZ	SPEAKERS (2) 6.5" Dual Cone Mounted in Both Doors, (2) 5.25" Dual Cone Mounted in Both B-Pillars
8RNB	CB RADIO Accommodation Package, Header Mounted, Feeds from Accessory Side of Ignition Switch, Includes Power Source, One Antenna and Antenna Base with Wiring on Left Side Mirror
8RPB	RADIO, STEERING WHEEL CONTROLS Mounted in Steering Wheel, Radio Function Control Switch, Includes Volume Up/Down, Mute, Forward/Back and Bluetooth Answer/Disconnect
8RPP	ANTENNA Shark Fin, Roof Mounted
8RPS	RADIO AM/FM/WB/Clock/Bluetooth/USB Input/Auxiliary Input
8THB	BACK-UP ALARM Electric, 102 dBA
8TKB	STOP, TURN, TAIL & B/U LIGHTS {Truck Lite} Super 44, with LED Lights for Stop, Turn & Tail Lights, Truck Lite Super 40 for Backup Lights, with Power Module, "International" Termination and Less Junction Box, Includes Incandescent License Plate Light
8TKK	TRAILER AUXILIARY FEED CIRCUIT for Electric Trailer Brake Accommodation/Air Trailer ABS; with 30 Amp Fuse and Relay, Controlled by Ignition Switch
8VAY	HORN, ELECTRIC Disc Style
8WBW	JUMP START STUD 12V, Remote Mounted
8WCK	POWER SOURCE, TERMINAL TYPE 2-Post
8WDB	BATTERY BOX Steel, with Plastic Cover, 30" Wide, 2-4 Battery Capacity, Mounted Left Side Back of Fuel Tank
8WGB	SOLENOID, AIR for Customer Use; Provides (2) Normally Closed Pilot Air Source, Approx. 4 CFM, Includes Latched Switch in Cab; Air Available Only with Key in "Ignition" or "Accessory" Position; Air Will Exhaust with Key in "Off" Position
8WGU	BATTERY BOX COVER Aluminum
8WPH	CLEARANCE/MARKER LIGHTS (5) {Truck Lite} Amber LED Lights, Flush Mounted on Cab or Sunshade
8WPZ	TEST EXTERIOR LIGHTS Pre-Trip Inspection will Cycle all Exterior Lamps Except Back-up Lights
8WRB	HEADLIGHTS ON W/WIPERS Headlights Will Automatically Turn On if Windshield Wipers are Turned On
8WWJ	INDICATOR, LOW COOLANT LEVEL with Audible Alarm
8WXB	HEADLIGHT WARNING BUZZER Sounds When Head Light Switch is on and Ignition Switch is in "Off" Position
8WZP	INDICATOR, BATTERY WARNING Green BATTERY ON Indicator, Mounted on Left Side of Instrument Panel, To be Used with Factory Installed or Customer Mounted Battery Disconnect Switch
8XAH	CIRCUIT BREAKERS Manual-Reset (Main Panel) SAE Type III with Trip Indicators, Replaces All Fuses
8XBK	SWITCH, AUXILIARY Switch 40 amp Circuit for Customer Use; Includes Wiring Connection at Power Distribution Center (PDC) and Control in Cab
8XGT	TURN SIGNALS, FRONT Includes LED Side Turn Lights Mounted on Fender
8XHD	BATTERY DISCONNECT SWITCH 300 Amp, Disconnects Charging Circuits, Locks with Padlock, Cab Mounted
8XHN	HORN, AIR Single Trumpet, Black, with Lanyard Pull Cord
8XKL	STARTING MOTOR {Mitsubishi Electric Automotive America 90P47} 12-Volt, with Soft-Start

<u>Code</u>	<u>Description</u>
8XKM	SWITCH, AIR HORN, PASSENGER Fire Truck Application; Momentary Switch Located in Instrument Panel Close to Passenger, Driver Also To Activate Switch with Lanyard
8XNZ	HEADLIGHTS Halogen, with Daytime Running Lights
8XPK	POWER SOURCE, ADDITIONAL Auxiliary Power Outlet (APO) with USB-A Port and USB-C Port, Located in the Instrument Panel
9585	FENDER EXTENSIONS Rubber
9AAB	LOGOS EXTERIOR Model Badges
9AAE	LOGOS EXTERIOR, ENGINE Badges
9HAN	INSULATION, UNDER HOOD for Sound Abatement
9HBM	GRILLE Stationary, Chrome
9HBN	INSULATION, SPLASH PANELS for Sound Abatement
9WAC	BUG SCREEN Mounted Behind Grille
9WBC	FRONT END Tilting, Fiberglass, with Three Piece Construction, for WorkStar/HV
10021	CHASSIS COATING Corrosion Resistant E-Coat Primer Coating for Single Frame Rails
10060	PAINT SCHEMATIC, PT-1 Single Color, Design 100
	<u>Includes</u> : PAINT SCHEMATIC ID LETTERS "WK"
10761	PAINT TYPE Base Coat/Clear Coat, 1-2 Tone
10AGB	COMMUNICATIONS MODULE Telematics Device with Over the Air Programming; Includes Five Year Data Plan and International 360
10BAE	LABEL, DEF "DEF ONLY"
10WCY	SAFETY TRIANGLES
10XAN	FIRE EXTINGUISHER 5 lb Class A B C
10XAP	FIRE EXTINGUISHER BRACKET Mounted Left Side Driver Seat
11001	CLUTCH Omit Item (Clutch & Control)
12703	ANTI-FREEZE Red, Extended Life Coolant; To -40 Degrees F/ -40 Degrees C, Freeze Protection
12849	BLOCK HEATER, ENGINE 120V/1000W, for Cummins ISB/B6.7/ISL/L9 Engines
	<u>Includes</u> : BLOCK HEATER SOCKET Receptacle Type; Mounted below Drivers Door
12EMZ	VENDOR WARRANTY, ENGINE {Cummins} B6.7 Engine, 3-Year Unlimited Miles Standard Warranty
12EXW	ENGINE, DIESEL {Cummins B6.7 280} EPA 2024, 280HP @ 2400 RPM, 660 lb-ft Torque @ 1600 RPM, 2600 RPM Governed Speed, 280 Peak HP (Max)
12THT	FAN DRIVE {Horton Drivemaster} Two-Speed Type, Direct Drive, with Residual Torque Device for Disengaged Fan Speed
	<u>Includes</u> : FAN Nylon
12UWZ	RADIATOR Aluminum, Cross Flow, Front to Back System, 1228 SqIn, with 1167 SqIn Charge Air Cooler, Includes In-Tank Oil Cooler
	<u>Includes</u>

<u>Code</u>	<u>Description</u>
	: DEAERATION SYSTEM with Surge Tank
	: HOSE CLAMPS, RADIATOR HOSES Gates Shrink Band Type; Thermoplastic Coolant Hose Clamps
	: RADIATOR HOSES Premium, Rubber
12VBC	AIR CLEANER Single Element
12VKB	EMISSION, CALENDAR YEAR {Cummins B6.7} EPA, OBD and GHG Certified for Calendar Year 2025
12VXT	THROTTLE, HAND CONTROL Engine Speed Control; Electronic, Stationary, Variable Speed; Mounted on Steering Wheel
12VYP	ENGINE CONTROL, REMOTE MOUNTED No Provision for Remote Mounted Engine Control
12WVG	EPA IDLE COMPLIANCE Low NOx Idle Engine, Complies with EPA Clean Air Regulations; Includes "Certified Clean Idle" Decal on Hood
12WZE	CARB IDLE COMPLIANCE Does Not Comply with California Clean Air Idle Regulations
12XCS	CARB EMISSION WARR COMPLIANCE Does Not Comply with CARB Emission Warranty
13BBJ	TRANSMISSION, AUTOMATIC {Allison 2500 RDS} 6th Generation Controls, Wide Ratio, 5-Speed with Overdrive, with PTO Provision, Less Retarder, with 33,000-lb GVW and GCW Max, On/Off Highway
13TKL	TRANSFER CASE {Meritor MTC-4208} 2-Speed, 8,300 lb-ft Torque Rating, Less PTO Provision, Electric Over Air Control, with Lube Pump
13WAW	OIL COOLER, TRANSMISSION {Modine} Water to Oil Type
13WDB	TRANSFER CASE LUBE {EmGard 50W} Synthetic; 1 thru 14.99 Pints
13WGC	OIL COOLER, TRANSMISSION with Oil Coolant Lines Routed to Oil Cooler
13WLN	TRANSMISSION OIL Synthetic; 20 thru 28 Pints
13WVS	TRANSMISSION SHIFT CONTROL T-Handle
13WVV	NEUTRAL AT STOP Allison Transmission Shifts to Neutral When Service Brake is Depressed and Vehicle is at Stop; Remains in Neutral Until Service Brake is Released
13WYY	SHIFT CONTROL PARAMETERS {Allison} 1000 or 2000 Series Transmissions, Performance Programming
13XAN	PTO LOCATION Customer Does Not Intend to Install PTO
14877	DIFFERENTIAL, LOCKING {Detroit Locker} No-Spin; for Dana Spicer (previously Eaton) Rear Axles
14AHE	AXLE, REAR, SINGLE {Dana Spicer S23-190} Single Reduction, Hypoid Gearing, 23,000-lb Capacity, R Wheel Ends . Gear Ratio: 6.14
14VAG	SUSPENSION, REAR, SINGLE 20,000-lb Capacity, Vari-Rate Springs, with 4500-lb Capacity Auxiliary Rubber Springs
14WMG	AXLE, REAR, LUBE {EmGard FE-75W-90} Synthetic Oil; 30 thru 39.99 Pints
15LMS	FUEL/WATER SEPARATOR 12 VDC Electric Heater, Includes Pre-Heater, Includes Water-in-Fuel Sensor, Cummins Supplied on Engine
15SRE	FUEL TANK Top Draw, Non-Polished Aluminum, D-Style, 19" Tank Depth, 50 US Gal (189L), Mounted Left Side, Under Cab
15WDG	DEF TANK 7 US Gal (26L) Capacity, Frame Mounted Outside Left Rail, Under Cab
16196	CAB Conventional 6-Man Crew Cab
16ATC	AUTOMATIC CLIMATE CONTROL Automatically Maintains Cabin Comfort Based on Selected Temperature
16BAM	AIR CONDITIONER with Integral Heater and Defroster
16GED	GAUGE CLUSTER Base Level; English with English Electronic Speedometer

Code	Description
	<u>Includes</u> : GAUGE CLUSTER DISPLAY: Base Level (3" Monochromatic Display), Premium Level (5" LCD Color Display); Odometer, Voltmeter, Diagnostic Messages, Gear Indicator, Trip Odometer, Total Engine Hours, Trip Hours, MPG, Distance to Empty/Refill for : GAUGE CLUSTER Speedometer, Tachometer, Engine Coolant Temp, Fuel Gauge, DEF Gauge, Oil Pressure Gauge, Primary and Secondary Air Pressure : WARNING SYSTEM Low Fuel, Low DEF, Low Oil Pressure, High Engine Coolant Temp, Low Battery Voltage (Visual and Audible), Low Air Pressure (Primary and Secondary)
16HCS	GAUGE, TEMPERATURE, AMBIENT Sensor Wiring with Display Unit Mounted in Cluster
16HGH	GAUGE, OIL TEMP, AUTO TRANS for Allison Transmission
16HGL	GAUGE, OIL TEMP, REAR AXLE
16HHE	GAUGE, AIR CLEANER RESTRICTION {Filter-Minder} Mounted in Instrument Panel
16HKT	IP CLUSTER DISPLAY On Board Diagnostics Display of Fault Codes in Gauge Cluster
16JNT	SEAT, DRIVER {National 2000} Air Suspension, High Back with Integral Headrest, Vinyl, Isolator, 1 Chamber Lumbar, with 2 Position Front Cushion Adjust, -3 to +14 Degree Angle Back Adjust
16LUM	SEAT, PASSENGER {National} Non Suspension, High Back with Integral Headrest, Vinyl, with Fixed Back, with Under Seat Storage
16SDC	GRAB HANDLE, EXTERIOR (2) Chrome, Towel Bar Type, with Anti-Slip Rubber Inserts, for Cab Entry Mounted Left and Right Side at B-Pillar
16SDZ	MIRROR, CONVEX, HOOD MOUNTED {Lang Mekra} (2) Right and Left Side, Bright, 7.5" Sq.
16SMT	SEAT, REAR {National} BENCH; Full Width; Vinyl, with Fixed Back and Two Integral Outboard Headrests
16SNV	MIRRORS (2) Aero Pedestal, Power Adjust, Heated, Turn Signals, Bright Heads, Black Arms, 6.5" x 14" Flat Glass, Includes 6.5" x 6" Convex Mirrors, for 102" Load Width
	<u>Notes</u> : Mirror Dimensions are Rounded to the Nearest 0.5"
16VCB	SEAT BELT All Orange; 4 to 6
16VKD	CAB INTERIOR TRIM Classic, for Crew Cab
	<u>Includes</u> : CONSOLE, OVERHEAD Molded Plastic with Dual Storage Pockets, Retainer Nets and CB Radio Pocket; Located Above Driver and Passenger : DOME LIGHT, CAB Door Activated and Push On-Off at Light Lens, Timed Theater Dimming, Integral to Overhead Console, Center Mounted : SUN VISOR (2) Padded Vinyl; 2 Moveable (Front-to-Side) Primary Visors, Driver Side with Toll Ticket Strap
16VLV	MONITOR, TIRE PRESSURE Omit
16WBY	ARM REST, RIGHT, DRIVER SEAT
16WEE	CAB SOUND INSULATION Includes Dash Insulator and Engine Cover Insulator
16WHJ	HOSE CLAMPS, HEATER HOSE {Breeze} Belleville Washer Type
16WJV	WINDOW, POWER (4) And Power Door Locks, Front and Rear Doors, Left and Right, Includes Express Down Feature
16WLS	FRESH AIR FILTER Attached to Air Intake Cover on Cowl Tray in Front of Windshield Under Hood
16WSK	CAB REAR SUSPENSION Air Bag Type
16XCW	CAB, INTERIOR TRIM, CLOSEOUT Under IP, Driver Side

<u>Code</u>	<u>Description</u>
16XJN	INSTRUMENT PANEL Flat Panel
16ZHY	ACCESS, CAB Aluminum, Self-Cleaning, Open and Serrated Design, Driver & Passenger Sides, Two Steps per Door, for use with Crew Cab
16ZPH	FLOOR, COATING LINE-X, Applied to Interior Cab Floor
26DWJ	WHEEL, SPARE, DISC {Accuride 42362} 24.5x8.25 Rims, Standard Polish Aluminum, 10-Stud, 285.75mm BC, Hub-Piloted
27DWJ	WHEELS, FRONT {Accuride 42362} DISC; 24.5x8.25 Rims, Standard Polish Aluminum, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs
28DWJ	WHEELS, REAR {Accuride 42362} DUAL DISC; 24.5x8.25 Rims, Standard Polish Aluminum, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs
7384225439	(2) TIRE, FRONT 11R24.5 Load Range H HSR 3 (CONTINENTAL), 473 rev/mile, 75 MPH, All-Position
7384225447	(4) TIRE, REAR 11R24.5 Load Range H HDL2 DL+ (CONTINENTAL), 468 rev/mile, 75 MPH, Drive

Services Section:

40128	WARRANTY Standard for HV507, HV50B, HV607 Models, Effective with Vehicles Built July 1, 2017 or Later, CTS-2025A
-------	--

<u>Description</u>	(US DOLLAR)	<u>Price</u>
Factory List Prices:		
Product Items	\$190,415.00	
Service Items	\$0.00	
Total Factory List Price Including Options:		\$190,415.00
Freight	\$3,100.00	
Total Freight:		\$3,100.00
Total Factory List Price Including Freight:		\$193,515.00
Less Customer Allowance:		(\$67,055.68)
Total Vehicle Price:		\$126,459.32
Total Sale Price:		\$126,459.32
Total Per Vehicle Sales Price:		\$126,459.32
Total Net Sales Excluding Taxes:		\$126,459.32
Documentation Fee	\$391.50	
Total Taxes:		\$391.50
Net Sales Price:		\$126,850.82

Please feel free to contact me regarding these specifications should your interests or needs change. I am confident you will be pleased with the quality and service of an International vehicle.

Approved by Seller:

Accepted by Purchaser:

Official Title and Date_____
Firm or Business Name_____
Authorized Signature_____
Authorized Signature and Date

This proposal is not binding upon the seller without
 Seller's Authorized Signature

Official Title and Date

The TOPS FET calculation is an estimate for reference purposes only. The seller or retailer is responsible for calculating and reporting/paying appropriate FET to the IRS.

The limited warranties applicable to the vehicles described herein are Navistar, Inc.'s standard printed warranties which are incorporated herein by reference and to which you have been provided a copy and hereby agree to their terms and conditions.



ITA Truck Sales & Service LLC
2835 NW EVANGELINE THRUWAY
LAFAYETTE LA 70507
Phone: (337) 234-9425
Dealer # N-2023-00246

Invoice

Contract Date: 12/03/2024
Deal #: DE-04205
Customer #: PROS-002795
Salesperson: Chris Ormond

Bill To: **PROS-002795**
TOWN OF JEAN LAFITTE
2654 JEAN LAFITTE BLVD
LAFITTE LA 70067-5204
P:(504) 689-2208

Ship To:
TOWN OF JEAN LAFITTE
2654 JEAN LAFITTE BLVD
LAFITTE, LA 70067-5204

Stock#: N252771 VIN:3HAEEMMNXL384987
New 2025 INTERNATIONAL HV507

Price: **\$126,459.32**

Total Price	\$126,459.32
Documentation Fee	\$391.50
Total	<u>\$126,850.82</u>

This agreement and any documents which are part of this transaction or incorporated herein comprise the entire agreement affecting this Retail Purchase Agreement and no other agreement or understanding of any nature concerning the same has been made or entered into or will be recognized. I have read and accept all of the terms and conditions of this Agreement, and agree to them as if they were printed above my signature. I further acknowledge receipt of a copy of this Agreement. This Agreement shall not become binding until signed and accepted by an Authorized Dealership Representative.

Purchaser's Signature

12/03/2024
Date

Chris Ormond
Sales Representative

Co-Purchaser's Signature

12/03/2024
Date

Manager's Signature

12/03/2024
Date

ITA Truck Sales & Service LLC
2835 NW EVANGELINE THRUWAY
LAFAYETTE LA 70507
Phone: (337) 234-9425
Dealer # N-2023-00246

Purchase Agreement

Contract Date: 12/03/2024

Deal #: DE-04205

Customer #: PROS-002795

Salesperson: Chris Ormond

Bill To: PROS-002795
TOWN OF JEAN LAFITTE
2654 JEAN LAFITTE BLVD
LAFITTE LA 70067-5204
P:(504) 689-2208

Ship To:
TOWN OF JEAN LAFITTE
2654 JEAN LAFITTE BLVD
LAFITTE, LA 70067-5204

Stock#: N252771 VIN:3HAEEMMXSL384987
New 2025 INTERNATIONAL HV507

Price: \$126,459.32

Total Price	\$126,459.32
Documentation Fee	\$391.50
Total	<u>\$126,850.82</u>

This agreement and any documents which are part of this transaction or incorporated herein comprise the entire agreement affecting this Retail Purchase Agreement and no other agreement or understanding of any nature concerning the same has been made or entered into or will be recognized. I have read and accept all of the terms and conditions of this Agreement, and agree to them as if they were printed above my signature. I further acknowledge receipt of a copy of this Agreement. This Agreement shall not become binding until signed and accepted by an Authorized Dealership Representative.

		12/03/2024	Chris Ormond
Purchaser's Signature	Date	Sales Representative	
		12/03/2024	12/03/2024
Co-Purchaser's Signature	Date	Manager's Signature	Date

DEAL # DE-04205

CUST # PROS-002795



2835 NW EVANGELINE THRUWAY
LAFAYETTE LA 70507
Phone: (337) 234-9425



www.ITA-Trucks.com

www.ideallease.com

Lafayette

New Orleans

Lake Charles

Houma

Slidell

Extended Warranty Waiver

Customer Name: TOWN OF JEAN LAFITTE

Year: 2025 Make: INTERNATIONAL Model: HV507

VIN: 3HAEEMMNXSL384987

☐

I/We will exercise the option to purchase extended warranty.



I/We hereby waive the option to purchase extended warranty.
I have read and understand the statement below.

ALL WARRANTIES, IF ANY, BY MANUFACTURER OR SUPPLIER OTHER THAN DEALER ARE THEIRS, NOT DEALER'S, AND SUCH MANUFACTURER OR OTHER SUPPLIER SHALL BE LIABLE FOR PERFORMANCE UNDER SUCH WARRANTIES, UNLESS DEALER FURNISHES BUYER WITH A SEPARATE WRITTEN WARRANTY OR SERVICE CONTRACT MADE BY DEALER ON ITS OWN BEHALF; DEALER HEREBY DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE: (A) ON ALL SERVICES SOLD BY DEALER; AND (B) ON ALL USED VEHICLES WHICH ARE HEREBY SOLD "AS IS-NOT EXPRESSLY WARRANTED OR GUARANTEED."

Customer Signature

12/03/2024

Date

**OnCommand® Connection OTA Programming Services
Company Administrator Authorization**

As the owner ("Customer") of vehicle(s) enrolled in OnCommand® Connection (OCC) ("the Company Vehicles"), I designate the individual identified below as Company Administrator with authority to assign permissions related to over-the-air (OTA) programming of engine calibrations and programmable parameters to OCC users with access to the Company Vehicles ("OTA Programming Services"), including

- Assign and revoke programmer access
- Enable and disable Auto-Deploy engine calibration updates
- Deploy engine calibration updates
- Create and deploy programmable parameter update profiles

Through the OTA Programming Services, I will receive the UPTIME™ benefits which OnCommand® Connection OTA Programming Services offer, including fast, timely updates no matter where the vehicle is located, greater flexibility to modify engine parameters for the right balance of performance, safety and efficiency, and more, as set forth in the OnCommand® Connection Terms of Service and the associated Privacy Policy located at <https://info.oncommandconnection.com/terms-of-use-and-privacy-policy>.

I understand that OTA Programming Services are available for the Company Vehicles as long as they are enrolled in OnCommand® Connection Telematics Services.

I represent that I have authority on behalf of the below Customer to make this designation and agree to the terms of the OnCommand® Connection Terms of Service and the associated Privacy Policy which I have had the opportunity to read and review.

Name, email and telephone number of the person who will serve as Company Administrator of the Company Vehicles:

Name*: TOWN OF JEAN LAFITTE

Email address*: ycrain@townofjeanlafitte.com

Telephone number*: (504) 689-2208

OCC User ID: _____

Signature on behalf of Customer*: _____ Date*: 12/03/2024

Name (printed)*: _____

Title*: _____

Customer Name*: TOWN OF JEAN LAFITTE DOT Number: _____

Customer Address*: 2654 JEAN LAFITTE BLVD LAFITTE LA 70067-5204

Customer CIS Number: _____

List of Company Vehicles (enter VIN of one or more Company Vehicles)*:

3HAEEMNXSL384987

* Required field

Bid Bond**CONTRACTOR:***(Name, legal status and address)*

ITA TRUCK SALES & SERVICE, L.L.C.
763 O'NEAL LANE, Baton Rouge, LA 70816
(252) 923-3450

SURETY:*(Name, legal status and principal place of business)*

Jet Insurance Company
6701 Carmel Rd Ste 250 Charlotte, NC 28226
8004381162

OWNER:*(Name, legal status and address)*

Town of Jean Lafitte
4917 City Park Drive

Lafitte LA 70067

BOND AMOUNT:

Not to Exceed: **One Hundred Twenty-six Thousand Eight Hundred Fifty (\$126,850.82) Dollars**

PROJECT:*(Name, location or address, and Project number, if any)*

2025 International Model HV507 Truck

The Contractor and Surety are bound to the Owner in the amount set forth above, for the payment of which the Contractor and Surety bind themselves, their heirs, executors, administrators, successors and assigns, jointly and severally, as provided herein. The conditions of this Bond are such that if the Owner accepts the bid of the Contractor within the time specified in the bid documents, or within such time period as may be agreed to by the Owner and Contractor, and the Contractor either (1) enters into a contract with the Owner in accordance with the terms of such bid, and gives such bond or bonds as may be specified in the bidding or Contract Documents, with a surety admitted in the jurisdiction of the Project and otherwise acceptable to the Owner, for the faithful performance of such Contract and for the prompt payment of labor and material furnished in the prosecution thereof; or (2) pays to the Owner the difference, not to exceed the amount of this Bond, between the amount specified in said bid and such larger amount for which the Owner may in good faith contract with another party to perform the work covered by said bid, then this obligation shall be null and void, otherwise to remain in full force and effect. The Surety hereby waives any notice of an agreement between the Owner and Contractor to extend the time in which the Owner may accept the bid. Waiver of notice by the Surety shall not apply to any extension exceeding sixty (60) days in the aggregate beyond the time for acceptance of bids specified in the bid documents, and the Owner and Contractor shall obtain the Surety's consent for an extension beyond sixty (60) days.

If this Bond is issued in connection with a subcontractor's bid to a Contractor, the term Contractor in this Bond shall be deemed to be Subcontractor and the term Owner shall be deemed to be Contractor.

When this Bond has been furnished to comply with a statutory or other legal requirement in the location of the Project, any provision in this Bond conflicting with said statutory or legal requirement shall be deemed deleted herefrom and provisions conforming to such statutory or other legal requirement shall be deemed incorporated herein. When so furnished, the intent is that this Bond shall be construed as a statutory bond and not as a common law bond.

Signed and sealed this **30th** day of **January** **2025**

ITA TRUCK SALES & SERVICE, L.L.C.

*(Principal)**(Seal)**(Witness)**(Title)*

Jet Insurance Company

(Surety)

David Gonsalves

Attorney In Fact

*(Title)**(Witness)*

Nick Brady



By arrangement with the American Institute of Architects, the National Association of Surety Bond Producers (NASBP) (www.nasbp.org) makes this form document available to its members, affiliates, and associates in Microsoft Word format for use in the regular course of surety business. NASBP vouches that the original text of this document conforms exactly to the text in AIA Document A310-2010, Bid Bond. Subsequent modifications may be made to the original text of this document by users, so careful review of its wording and consultation with an attorney are encouraged before its completion, execution or acceptance.



PO Box 471023
Charlotte, NC 28226
Phone: (800) 438-1162
Fax: (704) 364-3214

This form must be returned to The Bond Exchange within five (5) Business days after the release of the project bid results. We must notify the Surety.

Without these results, Final Payment and Performance bonds will not be approved.

Contractor's Name: ITA TRUCK SALES & SERVICE, L.L.C.

Project Name: 2025 International Model HV507 Truck

Bid Bond Number: BB540097

Bid Bond Estimate:

Date of Bid:

WERE YOU LOW BIDDER: ☐ YES ☐ NO

PLEASE COMPLETE THE FOLLOWING:

<u>BIDDER</u>	<u>AMOUNT</u>
Low Bid: _____	\$ _____
2 nd Bid: _____	\$ _____
3 rd Bid: _____	\$ _____

JET INSURANCE COMPANY

POWER OF ATTORNEY

NOW ALL BY THESE PRESENTS: That **JET INSURANCE COMPANY**, a corporation organized and existing under the laws of the State of North Carolina, having its principal office in Charlotte, North Carolina does hereby constitute and appoint

Name
David Gonsalves

Limit of Liability per Bond
\$126,850.82

its true and lawful Attorney(s)-in-fact to execute, seal and deliver for and on its behalf as surety, any and all bonds, undertakings, contracts of indemnity, recognizances and other writings obligatory in the nature thereof, which are or may be allowed, required or permitted by law, statute, rule, regulation, contract or otherwise, provided that the liability of such shall not exceed the limit stated above.

The execution of such instrument(s) in pursuance of these presents, shall be as binding upon **JET INSURANCE COMPANY** as fully and amply, to all intents and purposes, as if the same had been duly executed and acknowledged by its regularly elected officers at the principal office.

The Power of Attorney is executed and may be certified so, and may be revoked, pursuant to and by authority of the following resolutions adopted by the Board of Directors of **JET INSURANCE COMPANY** by unanimous written consent dated August 03, 2018, of which the following is a true excerpt:

RESOLVED that the President, or any Vice President, acting with any Secretary or Assistant Secretary, shall have power and authority to appoint Attorney(s)-in-fact, and to authorize them to execute on behalf of the Company, attach the Seal of the Company thereto and deliver, bonds, undertakings, contracts of indemnity, recognizances and other writings obligatory in the nature thereof; to prescribe their respective duties and the respective limits of their authority; and to revoke, at any time, any such Attorney-in-fact and revoke the authority given.

Further, this Power of Attorney is signed and sealed by facsimile pursuant to resolution of the Board of Directors of the Company adopted by unanimous written consent dated August 3, 2018, of which the following is a true excerpt:

RESOLVED that the signature of any authorized officer and the Seal of the Company may be affixed by facsimile to any Power of Attorney or certification thereof authorizing the execution on behalf of the Company and delivery of any bond, undertaking, contract of indemnity, recognizance and other writings obligatory in the nature thereof, and such signature and seal when so used shall have the same force and effect as though manually affixed.

IN WITNESS WHEREOF, **JET INSURANCE COMPANY** has caused this instrument to be signed and its corporate seal to be affixed by its authorized officer, this 17th day of May, 2023.



JET INSURANCE COMPANY

Spencer Silno

Richard Popp

STATE OF NORTH CAROLINA
County of Mecklenburg

Spencer Silno, President

Richard Popp, Secretary

On this 17th day of May, 2023 before me came the individuals who executed the preceding instrument, to me personally known, and being by me duly sworn, said that each is the herein described and authorized officer of Jet Insurance Company; that the seal affixed to said instrument is the Corporate Seal of said Company; that the Corporate Seal and each signature were duly affixed by order of the Board of Directors of said Company.

Sara C. Holt

Sara C. Holt
Notary Public, State of North Carolina
County of Mecklenburg
My Commission Expires 09/11/2027

IN WITNESS WHEREOF, I have hereunto set my hand at Jet Insurance Company offices the day and year above written.

SARA C. HOLT
Notary Public, North Carolina
Mecklenburg County
My Commission Expires
September 11, 2027

I, Richard Popp, Secretary of **JET INSURANCE COMPANY**, do hereby certify that the above and foregoing is a true and correct copy of a Power of Attorney executed by **JET INSURANCE COMPANY**, which is still in full force and effect.

IN WITNESS WHEREOF, I have thereunto set my hand and attached the seal of said Company this 30th day of January, 2025.



Richard Popp

Richard Popp, Secretary